

# Office Pro 1000/1500/2000 G2

Line-Interactive Protection from 1000VA to 2000VA

¢

## **IDEALLY SUITED FOR:**

**Computers and PCs Security Recording Devices VOIP and Telecom** Networking Equipment



Line Interactive design Automatic voltage regulation (AVR) FEATURE LCD provides real time status Eight outlets (4) Surge only (4) Battery Backup outlets High surge rating of 490 joules Network surge protection via RJ45 connection Stay informed with Free monitoring Software Easy change user replaceable batteries 37 Month Silver Warranty for electronics and battery Lifetime \$ 50,000 Equipment Protection Policy

S

## Office Pro 1000/1500/2000 G2

Line-Interactive Protection from 1000VA to 2000VA

#### **Rear View**



### **LCD Display**



LCD display indicates input voltage, output voltage, load level, battery capacity, operation mode, and alarm conditions.

8 hours to 90%

12VDC or 24VDC

. . .

### **Specifications:**

#### Office Pro 1000/1500/2000: 120V 50/60HZ

Model #	Rating (VA/Watts)	Input	Output Receptacles	Dim. HxWxD (in.)	Weight (lbs.)
OP1000U-G2	1000/600	5-15P	(4) 5-15R surge only (4) 5-15R battery & surge	7 x 5.5 x 12	22
OP1500U-G2	1500/900	5-15P	(4) 5-15R surge only (4) 5-15R battery & surge	7 x 5.5 x 12	22
OP2000U-G2	2000/1200	5-20P	(4) 5-15R surge only (4) 5-15R battery & surge	7 x 5.5 x 12	24

Electrical Input		Communications			
Nominal Voltage Voltage Range Frequency (HZ)	110 - 120V 82~148 50/60Hz (Auto-Sense)	Interface Type Monitoring / Shutdown Software	1 HID USB port Windows Vista/7/8/10. Included at no charge.		
Electrical Output		Environmental			
Voltage – On Inverter	110 - 120V	Operation Temperature	+32°F to + 104°F (0°C to + 40°C)		
Frequency (HZ) Wave Form	50/60Hz, (± 1 Hz) Utility –True Sine Wave Battery-Simulated Sine Wave	Relative Humidity	0% to 90%, non- condensing		
		Standards and Certification			
Warranty and Protection		Quality Assurance	ISO 9001 Certified		
Warranty	37 month Silver	Markings	UL 1778 / TUV		
	warranty on electronics and batteries.	Battery			
Load Protection Guarantee	\$ 50,000 (U.S. only)	Type Recharge time	Sealed lead acid 8 hours to 90%		

**Recharge time** 

Voltage

#### **Runtime Chart**

	Load (Watts) /	Load (Watts) / Time in minutes				
Model	300	600	900	1200		
OP1000U-G2	8.5 m	< 2m	N/A	N/A		
OP1500U-G2	17m	4.5m	< 2 m	N/A		
OP2000U-G2	20m	6.5m	3.5m	<2 m		



Orion Power Systems manufactures ups systems from 550va to 120kVA along with power strips, surge suppression, and communication accessories. Professionals in the IT, security, and telecommunications industries count on Orion Power Systems to provide power protection that is reliable and on budget.

> If you rely on clean power you can rely on Orion.... Just like these clients



Orion Power Systems, Inc. 3811 University Blvd. W Ste. 3 Jacksonville, FL 32217 Toll-Free: 877.385.1654 Fax: 877.659.8638 http://www.orionpowersystems.com